

MR-FPCH2316F1-UN40L0-CB0M0C

Marine Grade IP66 Full Fanless Panel PC Stainless Chassis, 23.1" LCD monitor, 1600 x 1200, LED 400 nits, Intel® Core™ Ultra Series 2 Processors (Arrow Lake)



Features

- Optional connector type: M12 Metal connectors, MIL-38999, MIL-26482 series connectors
- Intel® Core™ Ultra Series 2 Processors (Arrow Lake)
- Intel® Core™ Ultra 5, 7 Processors
- Intel® Arc™ 140T GPU
- Support 1 x DDR5 5600 MT/s SO-DIMM, Non-ECC, Max up to 32GB
- 1 x HDMI, 4 x USB3.2 Gbps, 4 x Giga LAN (Intel I210)
- Support TPM 2.0 onboard IC

Specification

Panel	
Cell Type	TFT LCD
Glass Surface	Black Anti-Glare, low reflection coating
Aspect Ratio	4 : 3
Size	23.1" viewable diagonal area
Active Area	470.4(H) x 352.8(V) mm
Pixel Pitch	0.294(H) x 0.294(V) mm
Native Resolution	1600(H) x 1200(V)
Colors	16.7 M
Brightness	400
Contrast	600 : 1
Response Time	≤ 8 ms (G-to-G)
Viewing Angle (typical)	H. 160°(- 0°~ + 0°) , V. 160°(- 0°~ + 0°)
Light Source	LED backlight, Long life, 35,000 hrs (typ)
Power	
Power Input	Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz
Power Consumption	

System	
CPU	Intel® Core™ Ultra 5, 7 Processors (Series 2)
BIOS	AMI UEFI BIOS
System / Graphic Chipset	Intel® Arc™ 140T GPU
System Memory	DDR5 5600 MT/s SO-DIMM, Non-ECC, Max up to 32GB
HDD	1, M.2 M-Key 2280, PCIe x4, NVMe x4 SSD.
I/O port	1xHDMI 4xUSB3.2 4xLAN, 1xLine-out
Expansion	PCIe/PCI expansion availability varies by model.
Dimensions	
Physical	Please refer to Drawing
Carton	TBD
Operating Condition	
Temperature / Humidity	

Options

Touch	Video Input	Enhanced Panel	Power	Others
Resistive Touch	AV-IN	High Brightness Panel	24V DC-IN	Motion Sensor
Projected Capacitive Touch	AV_Looping	Sunlight Readable	9~36V DC-IN	Light Sensor
Infrared Touch	HDMI / DP	Wide Viewing Angle	48V, 72V DC-IN	VR-knob Dimming
Protected Glass	HD-SDI	Wide Temperature	90V, 125V DC-IN	RS232 Remote On/Off
Optical Bonding		UV Film	110V, 220V DC-IN	Military Connector: MIL 38999
		Anti-Vandal		Metal Connector: M12 / M16
				Stainless 316 Enclosure

Winsonic®

Winsonic Electronics Co., Ltd.

Tel: +886-3-370-4789 Fax: +886-3-370-4722 E-mail: sales@ewinsonic.com

No.290-1, Wen Zhong Rd., Taoyuan City, Taoyuan County 33056, Taiwan (R.O.C.)